

certifire Letterplates

For 40–80mm Door Profiles

10
Year
Colour
fast

All Aluminium Letterplates

Finishes	Product Code	Material Construction	Coating Guarantee	Sizes
Gold Anodised	FMG1248G -CERTIFIRE	Aluminium	10 Years Colour Fast	Distance Between Screw Holes: 274mm
Silver Anodised	FMS1248S -CERTIFIRE	Aluminium	10 Years Colour Fast	Letterplate Length: 305mm
Polished Silver	FMPS1248PS -CERTIFIRE	Aluminium	10 Years Colour Fast	Letterplate Height: 76mm
				Letterplate Width: 40-80mm
				Cavity Hole Size: 260mm x 48mm



All Stainless Steel Letterplates

Finishes	Product Code	Material Construction	Coating Guarantee	Sizes
PVD Gold	FMSS1248PVDG -CERTIFIRE-NANOCOAST	Stainless Steel	Lifetime	Distance Between Screw Holes: 272mm
Mirror Polished	FMSS1248MPSS -CERTIFIRE-NANOCOAST	Stainless Steel	Lifetime	Letterplate Length: 305mm
Satin Stainless	FMSS1248SSS -CERTIFIRE-NANOCOAST	Stainless Steel	Lifetime	Letterplate Height: 76mm
				Letterplate Width: 40-80mm
				Cavity Hole Size: 260mm x 48mm



Stainless Steel



ANTI SNAP FLAP



ANTI VANDAL



ANTI BURGLAR

certifire Letterplates

For 40–80mm Door Profiles

Ultra Flexible Springs

30 min Fire Rated Approved Door Type: Non-metallic leaf (TT, ITT, ITM, ITC)

Outward facing, draft proof brushes

Outward facing brushes create the Anti-Vandal feature as it prevents vandals from placing unwanted items into the cavity

Outwards facing brushes also means better draught proofing and makes it easier to post letters through

An internal water seal prevents water getting into the door or panel, and stops letters getting wet

Conforms to many standards and testing requirements including BS EN 1303:2005

Blind bolts to the exterior

180° Opening

